

F AX9 S16*

Codice articolo: 808509104 / Female / *Prodotto disponibile su richiesta



Body size 3/8"	Valving style Flat face
Interchange ISO 16028	Sealing FKM (VITON)
Connection system Push	Disconnection system Pull back the sleeve
Material Stainless steel	Locking mechanism Locking ball + Safety lock
Disconnectable under pressure No	Thread MALE THREAD METRIC S - 24° CONE (ISO 8434-1 & DIN 2353)
Connectable under residual pressure No	Temperature -15 / +180 °C; +5 / +356 °F
Applications Oil & Gas, Industry, Cooling, Chemical & Food industry	

Performance	METRIC	Dimensions	METRIC
ISO DN (mm)	10	Port (A)	M24X1.5
Flow (l/min)	Da 20 a 50	Overall length M+F (mm)	132,6
Max. Flow suggested (l/min)	46	Length (mm)	76,2
Max. Operating pressure - coupled (Mpa)	35	Max. diameter (mm)	32
Operating pressure - uncoupled (mpa)	35	Weight (kg)	0,3
Connect force (N)	200		
Disconnect force (N)	45		
Spillage (ml)	0.01		

Related products

Item code	Type	Product name
808509105	Maschio	M AX9 S16

Caps

Item code	Product name
815100002	PLASTIC CAP F FF38 RED
815200002	PLASTIC FLIP CAP F FF38 RED
816005004	ALUMINUM CAP F FF38 NATURAL
815103002	PLASTIC CAP F FF38 BLACK**
815102002	PLASTIC CAP F FF38 BLUE**
815104002	PLASTIC CAP F FF38 GREEN**
815110002	PLASTIC CAP F FF38 MAGENTA**
815107002	PLASTIC CAP F FF38 ORANGE**
815101002	PLASTIC CAP F FF38 YELLOW**
815203002	PLASTIC FLIP CAP F FF38 BLACK**
815202002	PLASTIC FLIP CAP F FF38 BLUE**
815204002	PLASTIC FLIP CAP F FF38 GREEN**
815201002	PLASTIC FLIP CAP F FF38 YELLOW**

**Product available upon request