


F VR34 BSP*

Codice articolo: **809600000** / **Female** / ***Prodotto disponibile su richiesta**







Valving style Flat face non spill	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings ("Rohrleitung")	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Earthmoving, Vehicles

Performance	METRIC
ISO DN (mm)	20
Max. Flow suggested (l/min)	212
Max. Operating pressure - coupled (MPa)	35
Operating pressure - uncoupled (MPa)	35
Burst pressure - coupled (MPa)	140
Burst pressure - uncoupled (MPa)	100
Spillage (ml)	0.4
Manual connect torque (Nm)	2.2
Manual disconnect torque (Nm)	1.7

Dimensions	METRIC
Port (A)	3/4"
Overall length M+F (mm)	152,1
Length (mm)	88,1
Max. diameter (mm)	55
Weight (kg)	0,74

Related products

Item code	Type	Product name
809600001	Maschio	M VR34 BSP

Spare kits

Item code	Product name
815700914	SPARE KIT OR NBR+BK F VR34

Caps

Item code	Product name
814906016	ALUMINUM CAP F VR34 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service