







	Body size 2"	Valving style Flat face
	nterchange SO 16028	Sealing Nitrile NBR
	Connection system ush	Disconnection system Pull back the sleeve
	Material Farbon steel	Treatment Zn-Ni
	ocking mechanism ocking ball + Safety lock	Disconnectable under pressure No
М	'hread IALE THREAD METRIC L - 24° CONE (ISO 8434-1 & DIN 353)	Connectable under residual pressure No
	emperature 20 / +100 °C; -4 / +212 °F	Applications Earth moving, Agriculture, Vehicles, Oil & Gas, Industry, Hydraulic tools

Performance	IMPERIAL
ISO DN (mm)	12.5
Flow (gpm)	From 13,25 to 39,75
Max. Flow suggested (gpm)	23.85
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	4785
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	42.75
Disconnect force (lbf)	11.25
Spillage (ml)	0.02

Dimensions	IMPERIAL
Port (A)	M26x1.5
Overall length M+F (in)	5,34
Length (in)	2,83
Max. diameter (in)	1,38
Weight (lb)	0,53

Spare kits

Item code	Product name
815700339	SPARE KIT OR NBR+BK M FF 12

Caps

•	
Item code	Product name
815100029	PLASTIC CAP M FF12 RED
816005007	ALUMINUM CAP M FF12 NATURAL
815103029	PLASTIC CAP M FF12 BLACK**
815102029	PLASTIC CAP M FF12 BLUE**
815104029	PLASTIC CAP M FF12 GREEN**
815106031	PLASTIC CAP M FF12 GREEN RAL 6003 BIG RING **
815105029	PLASTIC CAP M FF12 WHITE**
815101029	PLASTIC CAP M FF12 YELLOW**

^{**}Product available upon request