
M/COUPLER VOF112 BSP

Codice articolo: **811200007** / **Coupler**





Valving style Poppet	**Body size** 1-1/2"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings (Oil&Gas)	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Earthmoving, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	40
Max. Flow suggested (gpm)	200.87
Max. Operating pressure - coupled (psi)	5002.5
Operating pressure - uncoupled (psi)	5002.5
Burst pressure - coupled (psi)	19995.5
Burst pressure - uncoupled (psi)	19995.5
Spillage (ml)	82.6
Manual connect torque (lbf ft)	29.48
Manual disconnect torque (lbf ft)	2.6532

Dimensions	IMPERIAL
Port (A)	1-1/2"
Overall length M+F (in)	8,67
Length (in)	5
Max. diameter (in)	5,71

Related products

Item code	Type	Product name
811200007	Coupler	M/COUPLER VOF112 BSP

Spare kits

Item code	Product name
815700963	SPARE KIT INTERNAL PARTS F-M VOF112

Caps

Item code	Product name
815405017	ALUMINUM CAP P VOF112 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service