
F/NIPPLE VOFX34 BSP

Codice articolo: **811200050 / Nipple**



Valving style Poppet	**Body size** 3/4"
Sealing Nitrile NBR	**Interchange** Similar couplings (Oil&Gas)
Connection system Screw	**Disconnection system** Unscrew
Material Stainless steel (AISI 316L)	**Locking mechanism** Screw to connect
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure Pressure in one side	**Temperature** -20 / +100 °C; -4 / +212 °F
Applications Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Marine, Others, Earthmoving, Oil & Gas	

Performance	IMPERIAL
ISO DN (mm)	20
Max. Flow suggested (gpm)	56.18
Max. Operating pressure - coupled (psi)	3001.5
Operating pressure - uncoupled (psi)	3001.5
Burst pressure - coupled (psi)	12006
Burst pressure - uncoupled (psi)	9004.5
Spillage (ml)	11.5
Manual connect torque (lbf ft)	1.6951
Manual disconnect torque (lbf ft)	1.6951

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	4,87
Length (in)	3,28
Max. diameter (in)	1,74
Weight (lb)	1,06

Related products

Item code	Type	Product name
811200050	Nipple	F/NIPPLE VOFX34 BSP

Spare kits

Item code	Product name
815700956	SPARE KIT OR NBR+BK F VOF34
815701146	SPARE KIT INTERNAL PARTS F-M VOFX34

Caps

Item code	Product name
815405012	ALUMINUM CAP N VOF34 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service