
F IRC12 BSP

Codice articolo: **812100004** / **Female**



Valving style Poppet	**Body size** 1/2"
Sealing Nitrile NBR	**Treatment** Zn-Ni
Interchange Similar couplings (Nordic)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety sleeve	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Earth Moving, Foundation, Material Handling, Road Construction, Hydraulic Tools, Earthmoving, Agriculture, Vehicles

Performance	IMPERIAL
ISO DN (mm)	12.5
Max. Flow suggested (gpm)	23.85
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	3625
Burst pressure - coupled (psi)	15950
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	27
Disconnect force (lbf)	7.875
Spillage (ml)	3.5

Dimensions	IMPERIAL
Port (A)	1/2"
Overall length M+F (in)	3,35
Length (in)	2,66
Max. diameter (in)	1,61
Weight (lb)	0,77

Related products

Item code	Type	Product name
812100005	Maschio	M IRC12 BSP

Spare kits

Item code	Product name
815700704	SPARE KIT OR NBR+BK F IRC12

Caps

Item code	Product name
815000046	PLASTIC CAP F IRC12 RED

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service