M IR34FA NPTF*

Codice articolo: **820002021** / **Male** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style Ball	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings (IR)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD NPTF (ANSI B.1.20.3)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance

	IMPERIAL
Max. Flow suggested (gpm)	152.64
Max. Operating pressure - coupled (psi)	3625
Operating pressure - uncoupled (psi)	2900
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	8700
Connect force (lbf)	42.75
Disconnect force (lbf)	10.125
Spillage (ml)	4.5

Dimensions

	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	4,19
Length (in)	2,09
Max. diameter (in)	1,54
Weight (lb)	0,42

Related products

Item code	Type	Product name
820002020	Femmina	F IR34FA NPTF

Caps

Item code	Product name
815001007	PLASTIC CAP M IR34 YELLOW**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service