# 1004-F/BSP

Codice articolo: **1004-F/BSP** / **Female**

| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>1/8" |
| **Sealing**<br>FKM (VITON) | **Interchange**<br>ISO 7241 B |
| **Connection system**<br>Pull back the sleeve and push | **Disconnection system**<br>Pull back the sleeve |
| **Material**<br>Stainless steel (AISI 316L) + Retainer in Brass | **Locking mechanism**<br>Locking ball |
| **Disconnectable under pressure**<br>No | **Thread**<br>FEMALE THREAD BSPP (ISO 1179-1) |
| **Connectable under residual pressure**<br>No | **Temperature**<br>-15 / +180 °C; +5 / +356 °F |
| **Applications**<br>Ceramic, Drilling Rig, Coil Tubing Unit, Chemical Pharma, Medical Devices, Others, Food & Beverage, Leather, Packaging, Paper, Robotics & Automation, Semiconductors, Oil & Gas | |

| Performance | METRIC |
|---|---|
| ISO DN (mm) | 5 |
| Max. Flow suggested (l/min) | 3 |
| Max. Operating pressure - coupled (MPa) | 25 |
| Burst pressure - coupled (MPa) | 75 |

## Related products

| Item code | Type | Product name |
|---|---|---|
| 1004-M/BSP | Maschio | 1004-M/BSP |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service