1006-F/NPT

Codice articolo: **1006-F/NPT / Female**

Valving style Poppet	**Body size** 1/4"
Sealing FKM (VITON)	**Interchange** ISO 7241 B
Connection system Pull back the sleeve and push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L) + Retainer in Brass	**Locking mechanism** Locking ball
Disconnectable under pressure No	**Thread** FEMALE THREAD NPT (ANSI B.1.20.1)
Connectable under residual pressure No	**Temperature** -15 / +180 °C; +5 / +356 °F
Applications Ceramic, Drilling Rig, Coil Tubing Unit, Chemical Pharma, Medical Devices, Others, Food & Beverage, Leather, Packaging, Paper, Robotics & Automation, Semiconductors, Oil & Gas	

Performance

	METRIC
ISO DN (mm)	6.3
Max. Flow suggested (l/min)	12
Max. Operating pressure - coupled (MPa)	25
Burst pressure - coupled (MPa)	75

Related products

Item code	Type	Product name
1006-M/NPT	Maschio	1006-M/NPT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service