4006-M/NPT

Codice articolo: **4006-M/NPT** / **Male**

Valving style Poppet	**Body size** 1/4"
Sealing FKM (VITON)	**Interchange** Innesti simili
Connection system Screw	**Disconnection system** Unscrew
Material Stainless steel (AISI 316L)	**Locking mechanism** Screw to connect
Disconnectable under pressure Yes	**Thread** FEMALE THREAD NPT (ANSI B.1.20.1)
Connectable under residual pressure Sì	**Temperature** -15 / +180 °C; +5 / +356 °F
Applications Road Construction, Semiconductors, Robotics & Automation, Paper, Packaging, Leather, Food & Beverage, Others, Medical Devices, Chemical Pharma, Material Handling, Foundation, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Earthmoving, Oil & Gas	

Performance	IMPERIAL
ISO DN (mm)	6.3
Max. Flow suggested (gpm)	152.64
Max. Operating pressure - coupled (psi)	9427
Burst pressure - coupled (psi)	23568

Related products

Item code	Type	Product name
4006-F/NPT	Femmina	4006-F/NPT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service