# 4013-F/NPT

Codice articolo: **4013-F/NPT / Female**

| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>1/2" |
| **Sealing**<br>FKM (VITON) | **Interchange**<br>Innesti simili |
| **Connection system**<br>Screw | **Disconnection system**<br>Unscrew |
| **Material**<br>Stainless steel (AISI 316L) | **Locking mechanism**<br>Screw to connect |
| **Disconnectable under pressure**<br>Yes | **Thread**<br>FEMALE THREAD NPT (ANSI B.1.20.1) |
| **Connectable under residual pressure**<br>Sì | **Temperature**<br>-15 / +180 °C; +5 / +356 °F |
| **Applications**<br>Road Construction, Semiconductors, Robotics & Automation, Paper, Packaging, Leather, Food & Beverage, Others, Medical Devices, Chemical Pharma, Material Handling, Foundation, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Earthmoving, Oil & Gas | |

| Performance | METRIC |
|---|---|
| ISO DN (mm) | 12.5 |
| Max. Flow suggested (l/min) | 45 |
| Max. Operating pressure - coupled (MPa) | 60 |
| Burst pressure - coupled (MPa) | 150 |

Related products

| Item code | Type | Product name |
|---|---|---|
| 4013-M/NPT | Maschio | 4013-M/NPT |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service