4013-F/NPT

Codice articolo: **4013-F/NPT** / **Female**

Valving style
Poppet

Body size
1/2"

Sealing
FKM (VITON)

Interchange
Innesti simili

Connection system
Screw

Disconnection system
Unscrew

Material
Stainless steel (AISI 316L)

Locking mechanism
Screw to connect

Disconnectable under pressure
Yes

Thread
FEMALE THREAD NPT (ANSI B.1.20.1)

Connectable under residual pressure
Si

Temperature
-15 / +180 °C; +5 / +356 °F

Applications
Road Construction, Semiconductors, Robotics & Automation, Paper, Packaging, Leather, Food & Beverage, Others, Medical Devices, Chemical Pharma, Material Handling, Foundation, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Earthmoving, Oil & Gas

Performance

	IMPERIAL
ISO DN (mm)	12.5
Max. Flow suggested (gpm)	152.64
Max. Operating pressure - coupled (psi)	8702
Burst pressure - coupled (psi)	21755

Related products

Item code	Type	Product name
4013-M/NPT	Maschio	4013-M/NPT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service