6025-F/BSP

Codice articolo: **6025-F/BSP** / **Female**

Valving style Flat face	**Body size** 3/4"
Sealing FKM (VITON)	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -15 / +180 °C; +5 / +356 °F
Applications Die Casting, Semiconductors, Robotics & Automation, Paper, Packaging, Leather, Food & Beverage, Laser, Electric Vehicles, Digital Transmitters, Injection Moulding, Others, Medical Devices, Chemical Pharma, Windmill, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Ceramic, Oil & Gas	

Performance	METRIC
ISO DN (mm)	25
Max. Flow suggested (l/min)	100
Max. Operating pressure - coupled (MPa)	15
Burst pressure - coupled (MPa)	45

Dimensions	METRIC
Port (A)	1"
Overall length M+F (mm)	154
Length (mm)	82
Max. diameter (mm)	48
Weight (kg)	0,4

Related products

Item code	Type	Product name
6025-M/BSP	Maschio	6025-M/BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service