F-VSB34 NPT

Codice articolo: **F-VSB34 NPT** / **Female**

Valving style Poppet	**Body size** 3/4"
Sealing Nitrile NBR	**Interchange** Innesti simili
Connection system Screw	**Disconnection system** Unscrew
Material Brass	**Locking mechanism** Screw to connect
Disconnectable under pressure No	**Thread** FEMALE THREAD NPT (ANSI B.1.20.1)
Connectable under residual pressure No	**Temperature** -20 / +100 °C; -4 / +212 °F
Applications Ceramic, Drilling Rig, Coil Tubing Unit, Chemical Pharma, Medical Devices, Others, Food & Beverage, Leather, Packaging, Paper, Robotics & Automation, Semiconductors, Oil & Gas	

Performance	METRIC
Max. Flow suggested (l/min)	62
Max. Operating pressure - coupled (MPa)	20

Dimensions	METRIC
Port (A)	3/4"
Overall length M+F (mm)	132
Length (mm)	78
Max. diameter (mm)	103

Related products

Item code	Type	Product name
M-VSB34 NPT	Maschio	M-VSB34 NPT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service