
Hydraulic Hose | Wire Braid

RIVAFLEX — DIN EN853 1SN

DIN EN 853 1 SN
Exceeds SAE100R1AT



Hose Construction:
Tube: oil resistant synthetic rubber
Reinforcement: one high tensile steel wire braid
Cover: abrasion and weather resistant synthetic rubber
Germanischer Lloyds Flame Resistant Certified
Temperature range: -40°C to +100°C (+120°C max.)

Part #	Nominal Ø		Inside Ø	Braid Ø	Outside Ø	Working pressure		Test pressure	Min burst pressure	Bend radius	Weight
	Dash	inch	mm	mm	mm	bar	psi	bar	bar	mm	kg/m
1SN-4	-4	1/4	6.4	11.1	13.4	225	3265	540	900	100	0.21
1SN-6	-6	3/8	9.5	15.1	17.4	180	2610	435	720	130	0.33
1SN-8	-8	1/2	12.7	18.3	20.6	160	2320	385	640	180	0.41
1SN-12	-12	3/4	19.0	25.4	27.7	105	1525	255	420	240	0.58
1SN-16	-16	1	25.4	33.3	35.6	88	1275	210	350	300	0.88

Stucchi FCP Pty Ltd. 8/7-11 Rodeo Drive - Dandenong South - VIC 3175 - Australia
Tel. +61 397934611 - Fax +61 397932216 - www.stucchiaustralia.com