
# M IR38 BSP

Codice articolo: **800000003** / **Male**




| | |
|---|---|
| **Valving style**<br>Ball | **Body size**<br>3/8" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 |
| **Interchange**<br>Similar couplings (IR) | **Connection system**<br>Pull back the sleeve and push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD BSPP (ISO 1179-1) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Agricultural Machinery, Agricultural Attachments, Agriculture |

| Performance | METRIC |
|---|---|
| Max. Flow suggested (l/min) | 46 |
| Max. Operating pressure - coupled (Mpa) | 30 |
| Operating pressure - uncoupled (MPa) | 30 |
| Burst pressure - coupled (MPa) | 100 |
| Burst pressure - uncoupled (MPa) | 100 |
| Connect force (N) | 125 |
| Disconnect force (N) | 45 |
| Spillage (ml) | 0.45 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 3/8" |
| Overall length M+F (mm) | 76,3 |
| Length (mm) | 38 |
| Max. diameter (mm) | 19 |
| Weight (kg) | 0,08 |

Related products

| Product code | Type | Product name |
|---|---|---|
| 800000002 | Femmina | F IR38 BSP |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service