
F IR38V BSP

Codice articolo: **800100002** / **Female**



Valving style Poppet	**Body size** 3/8"
Sealing FKM (VITON)	**Treatment** Cr3
Interchange Similar couplings (IR-V)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -15 / +180 °C; +5 / +356 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
Max. Flow suggested (l/min)	46
Max. Operating pressure - coupled (Mpa)	30
Operating pressure - uncoupled (MPa)	30
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	100
Connect force (N)	120
Disconnect force (N)	35
Spillage (ml)	1.3

Dimensions	METRIC
Port (A)	3/8"
Overall length M+F (mm)	76,3
Length (mm)	58,3
Max. diameter (mm)	34
Weight (kg)	0,22

Related products

Product code	Type	Product name
800100003	Maschio	M IR38V BSP

Spare kits

Product code	Product name
815700350	SPARE KIT OR NBR F IR38

Caps

Product code	Product name
815000014	PLASTIC PLUG F ISO-A 38 RED
815001014	PLASTIC PLUG F ISO-A 38 YELLOW*
815002014	PLASTIC PLUG F ISO-A 38 BLUE*
815003014	PLASTIC PLUG F ISO-A 38 BLACK*
815004014	PLASTIC PLUG F ISO-A 38 GREEN*
815005014	PLASTIC PLUG F ISO-A 38 WHITE*
815007014	PLASTIC PLUG F ISO-A 38 ORANGE*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service