M IV38HP BSP*

Codice articolo: **800200029** / **Male** / ***Prodotto disponibile su richiesta**

Valving style Ball	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO14540 (High pressure)	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Rescue Equipment, Utensili idraulici

Performance	METRIC
Max. Flow suggested (l/min)	23
Max. Operating pressure - coupled (Mpa)	70

Dimensions	METRIC
Port (A)	1/2"
Overall length M+F (mm)	F+D-25,4
Length (mm)	40
Max. diameter (mm)	35
Weight (kg)	0,14

Caps

Product code	Product name
815603013	PLASTIC CAP M IVHP38 BLACK
815605003	STEEL CAP M IVHP38 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service