F BIR100 SAE*

Codice articolo: **800504008** / **Female** / ***Prodotto disponibile su richiesta**

Valving style Poppet	**Body size** 1"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Foundation, Material Handling, Road Construction, Earth moving, Agriculture

Performance	METRIC
ISO DN (mm)	25
Max. Flow suggested (l/min)	200
Max. Operating pressure - coupled (Mpa)	23
Operating pressure - uncoupled (MPa)	23
Burst pressure - coupled (MPa)	80
Burst pressure - uncoupled (MPa)	80
Connect force (N)	190
Disconnect force (N)	55
Spillage (ml)	9

Dimensions	METRIC
Port (A)	1-5/16-12UN
Overall length M+F (mm)	127,3
Length (mm)	97,1
Max. diameter (mm)	54
Weight (kg)	0,76

Related products

Product code	Type	Product name
800504009	Maschio	M BIR100 SAE

Spare kits

Product code	Product name
815700178	SPARE KIT OR NBR+BK F BIR100

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service