
M IRB100 BSP

Codice articolo: **800600011 / Male**



Valving style Poppet	**Body size** 1"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 B	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Foundation, Material Handling, Road Construction, Steel Mill, Test Bench, Hydraulic Power Units, Earth moving, Agriculture, Oil & Gas

Performance	METRIC
ISO DN (mm)	25
Max. Flow suggested (l/min)	200
Max. Operating pressure - coupled (Mpa)	18
Operating pressure - uncoupled (MPa)	18
Burst pressure - coupled (MPa)	80
Burst pressure - uncoupled (MPa)	80
Connect force (N)	130
Disconnect force (N)	45
Spillage (ml)	14

Dimensions	METRIC
Port (A)	1"
Overall length M+F (mm)	133,2
Length (mm)	66
Max. diameter (mm)	37,7
Weight (kg)	0,33

Related products

Product code	Type	Product name
800600010	Femmina	F IRB100 BSP

Caps

Product code	Product name
815000041	PLASTIC CAP M ISO-B 100 RED
815003041	PLASTIC CAP M ISO-B 100 BLACK *

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service