
F IRB14V BSP*

Codice articolo: **800600102** / **Female** / ***Prodotto disponibile su richiesta**



Valving style Poppet	**Body size** 1/4"
Sealing FKM (VITON)	**Treatment** Cr3
Interchange ISO 7241 B	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -15 / +180 °C; +5 / +356 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Foundation, Material Handling, Road Construction, Steel Mill, Test Bench, Hydraulic Power Units, Earth moving, Agriculture, Oil & Gas

Performance	METRIC
ISO DN (mm)	6.3
Max. Flow suggested (l/min)	24
Max. Operating pressure - coupled (Mpa)	35
Operating pressure - uncoupled (MPa)	35
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	100
Connect force (N)	50
Disconnect force (N)	35
Spillage (ml)	0.33

Dimensions	METRIC
Port (A)	1/4"
Overall length M+F (mm)	70,7
Length (mm)	57
Max. diameter (mm)	27
Weight (kg)	0,12

Related products

Product code	Type	Product name
800600103	Maschio	M IRB14V BSP

Spare kits

Product code	Product name
815700216	SPARE KIT OR VITON+BK F ISOB 14

Caps

Product code	Product name
815000032	PLASTIC PLUG F ISO-B 14 RED
815003032	PLASTIC PLUG F ISO-B 14 BLACK**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service