F IRB38V BSP*

Codice articolo: **800600104** / **Female** / ***Prodotto disponibile su richiesta**

Valving style Poppet	**Body size** 3/8"
Sealing FKM (VITON)	**Treatment** Cr3
Interchange ISO 7241 B	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -15 / +180 °C; +5 / +356 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Foundation, Material Handling, Road Construction, Steel Mill, Test Bench, Hydraulic Power Units, Earth moving, Agriculture, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	10
Max. Flow suggested (gpm)	12.19
Max. Operating pressure - coupled (psi)	4350
Operating pressure - uncoupled (psi)	4350
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	18
Disconnect force (lbf)	10.125
Spillage (ml)	2.2

Dimensions	IMPERIAL
Port (A)	3/8"
Overall length M+F (in)	3,26
Length (in)	2,6
Max. diameter (in)	1,34
Weight (lb)	0,49

Related products

Product code	Type	Product name
800600105	Maschio	M IRB38V BSP

Spare kits

Product code	Product name
815700218	SPARE KIT OR VITON+BK F ISOB 38

Caps

Product code	Product name
815000034	PLASTIC PLUG F ISO-B 38 RED
815003034	PLASTIC PLUG F ISO-B 38 BLACK**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service