F A15 3/4 NPT

Codice articolo: **801301014** / **Female**

Valving style Flat face	**Body size** 5/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread FEMALE THREAD NPT (ANSI B.1.20.1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Earth moving, Agriculture, Vehicles, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	16
Max. Flow suggested (gpm)	39.22
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	4785
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	42.75
Disconnect force (lbf)	12.375
Spillage (ml)	0.02

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	5,49
Length (in)	3,31
Max. diameter (in)	1,65
Weight (lb)	1,39

Caps

Product code	Product name
815100008	PLASTIC CAP F FF58 RED
815200006	PLASTIC FLIP CAP F FF58 RED
816005008	ALUMINUM CAP F FF58 NATURAL
815101008	PLASTIC CAP F FF58 YELLOW*
815102008	PLASTIC CAP F FF58 BLUE*
815103008	PLASTIC CAP F FF58 BLACK*
815104008	PLASTIC CAP F FF58 GREEN*
815105008	PLASTIC CAP F FF58 WHITE*
815107008	PLASTIC CAP F FF58 ORANGE*
815110008	PLASTIC CAP F FF58 MAGENTA*
815201006	PLASTIC FLIP CAP F FF58 YELLOW*
815202006	PLASTIC FLIP CAP F FF58 BLUE*
815203006	PLASTIC FLIP CAP F FF58 BLACK*
815204006	PLASTIC FLIP CAP F FF58 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service