
M A7 3/8 SAE

Codice articolo: **801304017** / **Male**



Valving style Flat face	**Body size** 1/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Material Handling, Robotics & Automation, Paper, Packaging, Leather, Utensili idraulici, Hydraulic Power Units, Injection Moulding, Die Casting, Others, Test Bench, Steel Mill, Rail, Road Construction, Foundation, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Agricultural Attachments, Agricultural Machinery, Earth moving, Agriculture, Vehicles, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	6.3
Max. Flow suggested (gpm)	6.36
Max. Operating pressure - coupled (psi)	6090
Operating pressure - uncoupled (psi)	6090
Burst pressure - coupled (psi)	18270
Burst pressure - uncoupled (psi)	18270
Connect force (lbf)	33.75
Disconnect force (lbf)	10.125
Spillage (ml)	0.01

Dimensions	IMPERIAL
Port (A)	9/16-18UNF
Overall length M+F (in)	3,79
Length (in)	2
Max. diameter (in)	0,63
Weight (lb)	0,2

Related products

Product code	Type	Product name
801304004	Femmina	F A7 3/8 SAE

Spare kits

Product code	Product name
815700519	SPARE KIT OR NBR+BK M FF 14

Caps

Product code	Product name
815100023	PLASTIC CAP M FF14 RED
816005003	ALUMINUM CAP M FF14 NATURAL
815101023	PLASTIC CAP M FF14 YELLOW*
815102023	PLASTIC CAP M FF14 BLUE*
815103023	PLASTIC CAP M FF14 BLACK*
815104023	PLASTIC CAP M FF14 GREEN*
815105023	PLASTIC CAP M FF14 WHITE*
815107023	PLASTIC CAP M FF14 ORANGE*
815110023	PLASTIC CAP M FF14 MAGENTA*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service