M A15 3/4 ORFS*

Codice articolo: **801313021** / **Male** / ***Prodotto disponibile su richiesta**

Valving style Flat face	**Body size** 5/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread MALE THREAD ORFS (SAE J1453 or ISO 8434-3)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Earth moving, Agriculture, Vehicles, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	16
Max. Flow suggested (gpm)	39.22
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	4785
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	42.75
Disconnect force (lbf)	12.375
Spillage (ml)	0.02

Dimensions	IMPERIAL
Port (A)	1-3/16-12UN
Overall length M+F (in)	5,8
Length (in)	3,07
Max. diameter (in)	1,52
Weight (lb)	0,71

Related products

Product code	Type	Product name
801313020	Femmina	F A15 3/4 ORFS

Spare kits

Product code	Product name
815700341	SPARE KIT OR NBR+BK M FF 58

Caps

Product code	Product name
815100011	PLASTIC CAP M FF58 RED
816005009	ALUMINUM CAP M FF58 NATURAL
815101011	PLASTIC CAP M FF58 YELLOW**
815102011	PLASTIC CAP M FF58 BLUE**
815103011	PLASTIC CAP M FF58 BLACK**
815104011	PLASTIC CAP M FF58 GREEN**
815105011	PLASTIC CAP M FF58 WHITE**
815107011	PLASTIC CAP M FF58 ORANGE**
815110011	PLASTIC CAP M FF58 MAGENTA**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service