M FL15N 3/4 BSP*

Codice articolo: **802400011** / **Male** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style Flat face	**Body size** 5/8"
Sealing Nitrile NBR	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -20 / +100 °C; -4 / +212 °F
Applications Medical Devices, Semiconductors, Packaging, Food & Beverage, Laser, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas	

Performance	METRIC
ISO DN (mm)	16
Max. Flow suggested (l/min)	148
Max. Operating pressure - coupled (Mpa)	35
Operating pressure - uncoupled (MPa)	30
Burst pressure - coupled (MPa)	120
Burst pressure - uncoupled (MPa)	100
Connect force (N)	200
Disconnect force (N)	60
Spillage (ml)	0.03

Dimensions	METRIC
Port (A)	3/4"
Overall length M+F (mm)	133,8
Length (mm)	70,5
Max. diameter (mm)	27
Weight (kg)	0,28

Related products

Product code	Type	Product name
802400010	Femmina	F FL15N 3/4 BSP

Spare kits

Product code	Product name
815700341	SPARE KIT OR NBR+BK M FF 58

Caps

Product code	Product name
815100011	PLASTIC CAP M FF58 RED
816005009	ALUMINUM CAP M FF58 NATURAL
815101011	PLASTIC CAP M FF58 YELLOW**
815102011	PLASTIC CAP M FF58 BLUE**
815103011	PLASTIC CAP M FF58 BLACK**
815104011	PLASTIC CAP M FF58 GREEN**
815105011	PLASTIC CAP M FF58 WHITE**
815107011	PLASTIC CAP M FF58 ORANGE**
815110011	PLASTIC CAP M FF58 MAGENTA**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service