


F FL17N 1 BSP*

Codice articolo: **802400012** / **Female** / ***Prodotto disponibile su richiesta**











Valving style Flat face	**Body size** 3/4"
Sealing Nitrile NBR	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -20 / +100 °C; -4 / +212 °F

Applications
Medical Devices, Semiconductors, Packaging, Food & Beverage, Laser, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	19
Max. Flow suggested (gpm)	5.3
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	1740
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	6960
Connect force (lbf)	45
Disconnect force (lbf)	13.5
Spillage (ml)	0.03

Dimensions	IMPERIAL
Port (A)	1"
Overall length M+F (in)	6,04
Length (in)	3,66
Max. diameter (in)	1,89
Weight (lb)	1,75

Related products

Product code	Type	Product name
802400013	Maschio	M FL17N 1 BSP

Caps

Product code	Product name
815100010	PLASTIC CAP F FF34 RED
815200008	PLASTIC FLIP CAP F FF34 RED
816005010	ALUMINUM CAP F FF34 NATURAL
815101010	PLASTIC CAP F FF34 YELLOW**
815102010	PLASTIC CAP F FF34 BLUE**
815103010	PLASTIC CAP F FF34 BLACK**
815104010	PLASTIC CAP F FF34 GREEN**
815105010	PLASTIC CAP F FF34 WHITE**
815107006	PLASTIC CAP F FF34 ORANGE**
815110006	PLASTIC CAP F FF34 MAGENTA**
815201008	PLASTIC FLIP CAP F FF34 YELLOW**
815202008	PLASTIC FLIP CAP F FF34 BLUE**
815203008	PLASTIC FLIP CAP F FF34 BLACK**
815204008	PLASTIC FLIP CAP F FF34 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service