F FL30N 1-1/2 BSP*

Codice articolo: **802400016** / **Female** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style Flat face	**Body size** 1-1/2"
Sealing Nitrile NBR	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -20 / +100 °C; -4 / +212 °F
Applications Medical Devices, Semiconductors, Packaging, Food & Beverage, Laser, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas	

Performance

	METRIC
ISO DN (mm)	38
Max. Flow suggested (l/min)	750
Max. Operating pressure - coupled (Mpa)	23
Operating pressure - uncoupled (MPa)	8
Burst pressure - coupled (MPa)	80
Burst pressure - uncoupled (MPa)	32
Connect force (N)	580
Disconnect force (N)	160
Spillage (ml)	0.05

Dimensions

	METRIC
Port (A)	1-1/2"
Overall length M+F (mm)	214,8
Length (mm)	132,4
Max. diameter (mm)	80
Weight (kg)	2,91

Related products

Product code	Type	Product name
802400017	Maschio	M FL30N 1-1/2 BSP

Caps

Product code	Product name
815105014	ALUMINUM CAP F FF112 NATURAL
815100014	ALUMINUM CAP F FF112 RED**
815101014	ALUMINUM CAP F FF112 YELLOW**
815102014	ALUMINUM CAP F FF112 BLUE**
815103014	ALUMINUM CAP F FF112 BLACK**
815104014	ALUMINUM CAP F FF112 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service