
F FL45N 2? BSP*

Codice articolo: **802400018** / **Female** / ***Prodotto disponibile su richiesta**



Valving style Flat face	**Body size** 2"
Sealing Nitrile NBR	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -20 / +100 °C; -4 / +212 °F
Applications Medical Devices, Semiconductors, Packaging, Food & Beverage, Laser, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas	

Performance	METRIC
Max. Flow suggested (l/min)	1000
Max. Operating pressure - coupled (Mpa)	15
Operating pressure - uncoupled (MPa)	7
Burst pressure - coupled (MPa)	60
Burst pressure - uncoupled (MPa)	28
Connect force (N)	490
Disconnect force (N)	70
Spillage (ml)	0.1

Dimensions	METRIC
Port (A)	2"
Overall length M+F (mm)	241,5
Length (mm)	156,6
Max. diameter (mm)	100
Weight (kg)	5,23

Related products

Product code	Type	Product name
802400019	Maschio	M FL45N 2? BSP

Caps

Product code	Product name
815105016	ALUMINUM CAP F FF200 NATURAL
815100016	ALUMINUM CAP F FF200 RED **
815101016	ALUMINUM CAP F FF200 YELLOW **
815102016	ALUMINUM CAP F FF200 BLUE **
815103016	ALUMINUM CAP F FF200 BLACK **
815104016	ALUMINUM CAP F FF200 GREEN **

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service