
M FL45 2 BSP

Codice articolo: **802400119** / **Male**



Valving style Flat face	**Body size** 2"
Sealing FKM (VITON)	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -15 / +180 °C; +5 / +356 °F

Applications
Medical Devices, Semiconductors, Packaging, Food & Beverage, Laser, HVAC/R, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas

Performance	IMPERIAL
Max. Flow suggested (gpm)	265
Max. Operating pressure - coupled (psi)	2175
Operating pressure - uncoupled (psi)	2175
Burst pressure - coupled (psi)	8700
Burst pressure - uncoupled (psi)	8700
Connect force (lbf)	110.25
Disconnect force (lbf)	15.75
Spillage (ml)	0.1

Dimensions	IMPERIAL
Port (A)	2"
Overall length M+F (in)	9,51
Length (in)	4,87
Max. diameter (in)	2,87
Weight (lb)	1,74

Related products

Product code	Type	Product name
802400118	Femmina	F FL45 2 BSP

Spare kits

Product code	Product name
815700798	SPARE KIT OR VITON+BK M FF 200*

Caps

Product code	Product name
815105019	ALUMINUM CAP M FF200 NATURAL
815100019	ALUMINUM CAP M FF200 RED*
815101019	ALUMINUM CAP M FF200 YELLOW*
815102019	ALUMINUM CAP M FF200 BLUE*
815103019	ALUMINUM CAP M FF200 BLACK*
815104019	ALUMINUM CAP M FF200 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service