
# F FL4 1/8 BSP

Codice articolo: **802400122** / **Female**




| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>1/8" |
| **Sealing**<br>FKM (VITON) | **Interchange**<br>ISO 16028 |
| **Connection system**<br>Push | **Disconnection system**<br>Pull back the sleeve |
| **Material**<br>Stainless steel (AISI 316L) | **Locking mechanism**<br>Locking ball + Safety lock |
| **Disconnectable under pressure**<br>No | **Thread**<br>FEMALE THREAD BSPP (ISO 1179-1) |
| **Connectable under residual pressure**<br>No | **Temperature**<br>-15 / +180 °C; +5 / +356 °F |
| **Applications**<br>Medical Devices, Semiconductors, Packaging, Food & Beverage, Laser, HVAC/R, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas | |

| Performance | METRIC |
|---|---|
| Max. Flow suggested (l/min) | 6 |
| Max. Operating pressure - coupled (Mpa) | 35 |
| Operating pressure - uncoupled (MPa) | 33 |
| Burst pressure - coupled (MPa) | 140 |
| Burst pressure - uncoupled (MPa) | 120 |
| Connect force (N) | 140 |
| Disconnect force (N) | 30 |
| Spillage (ml) | 0.01 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 1/8" |
| Overall length M+F (mm) | 68,4 |
| Length (mm) | 40 |
| Max. diameter (mm) | 20 |
| Weight (kg) | 0,07 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 802400123 | Maschio | M FL4 1/8 BSP |

## Caps

| Product code | Product name |
|---|---|
| 815100021 | PLASTIC CAP M FF18 RED |
| 815101021 | PLASTIC CAP M FF18 YELLOW* |
| 815102021 | PLASTIC CAP M FF 18 BLUE* |
| 815103021 | PLASTIC CAP M FF 18 BLACK* |
| 815104021 | PLASTIC CAP M FF 18 GREEN* |
| 815105021 | PLASTIC CAP M FF 18 WHITE* |

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service