M FL30E 1-1/2 BSP*

Codice articolo: **802400215** / **Male** / ***Prodotto disponibile su richiesta**

Valving style Flat face	**Body size** 1-1/2"
Sealing EPDM	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F

Applications
Medical Devices, Semiconductors, Packaging, Food & Beverage, Laser, HVAC/R, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	38
Max. Flow suggested (gpm)	198.75
Max. Operating pressure - coupled (psi)	3335
Operating pressure - uncoupled (psi)	3335
Burst pressure - coupled (psi)	11600
Burst pressure - uncoupled (psi)	10150
Connect force (lbf)	130.5
Disconnect force (lbf)	36
Spillage (ml)	0.05

Dimensions	IMPERIAL
Port (A)	1-1/2"
Overall length M+F (in)	8,46
Length (in)	4,37
Max. diameter (in)	2,24
Weight (lb)	0,88

Related products

Product code	Type	Product name
802400214	Femmina	F FL30E 1-1/2 BSP

Spare kits

Product code	Product name
815700529	SPARE KIT OR EPDM+BK M FF 112**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service