F FL30K 1-1/2 BSP*

Codice articolo: **802400708** / **Female** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style Flat face	**Body size** 1-1/2"
Sealing KALREZ	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -25 / +300 °C; -13 / +572 °F
Applications Drilling Rig, Coil Tubing Unit, Data Center, Rail, Steel Mill, Test Bench, Windmill, Chemical Pharma, Others, Die Casting, Injection Moulding, Digital Transmitters, Electric Vehicles, Laser, Food & Beverage, Oil & Gas	

Performance	IMPERIAL
ISO DN (mm)	38
Max. Flow suggested (gpm)	198.75
Max. Operating pressure - coupled (psi)	725
Operating pressure - uncoupled (psi)	725
Burst pressure - coupled (psi)	5800
Burst pressure - uncoupled (psi)	4640
Connect force (lbf)	130.5
Disconnect force (lbf)	36
Spillage (ml)	0.05

Dimensions	IMPERIAL
Port (A)	1-1/2"
Overall length M+F (in)	8,46
Length (in)	5,21
Max. diameter (in)	3,15
Weight (lb)	1,74

Related products

Product code	Type	Product name
802400709	Maschio	M FL30K 1-1/2 BSP

Caps

Product code	Product name
815105014	ALUMINUM CAP F FF112 NATURAL
815100014	ALUMINUM CAP F FF112 RED**
815101014	ALUMINUM CAP F FF112 YELLOW**
815102014	ALUMINUM CAP F FF112 BLUE**
815103014	ALUMINUM CAP F FF112 BLACK**
815104014	ALUMINUM CAP F FF112 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service