F FL15E 3/4 NPT*

Codice articolo: **802401210** / **Female** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style
Flat face

Body size
5/8"

Sealing
EPDM

Interchange
ISO 16028

Connection system
Push

Disconnection system
Pull back the sleeve

Material
Stainless steel (AISI 316L)

Locking mechanism
Locking ball + Safety lock

Disconnectable under pressure
No

Thread
FEMALE THREAD NPT (ANSI B.1.20.1)

Connectable under residual pressure
No

Temperature
-40 / +150 °C; -40 / +302 °F

Applications
Medical Devices, Semiconductors, Packaging, Food & Beverage, Laser, HVAC/R, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	16
Max. Flow suggested (gpm)	39.22
Max. Operating pressure - coupled (psi)	5075
Operating pressure - uncoupled (psi)	1740
Burst pressure - coupled (psi)	17400
Burst pressure - uncoupled (psi)	6960
Connect force (lbf)	45
Disconnect force (lbf)	13.5
Spillage (ml)	0.03

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	5,27
Length (in)	3,19
Max. diameter (in)	1,65
Weight (lb)	1,09

Related products

Product code	Type	Product name
802401211	Maschio	M FL15E 3/4 NPT

Caps

Product code	Product name
815100008	PLASTIC CAP F FF58 RED
815200006	PLASTIC FLIP CAP F FF58 RED
816005008	ALUMINUM CAP F FF58 NATURAL
815101008	PLASTIC CAP F FF58 YELLOW**
815102008	PLASTIC CAP F FF58 BLUE**
815103008	PLASTIC CAP F FF58 BLACK**
815104008	PLASTIC CAP F FF58 GREEN**
815105008	PLASTIC CAP F FF58 WHITE**
815107008	PLASTIC CAP F FF58 ORANGE**
815110008	PLASTIC CAP F FF58 MAGENTA**
815201006	PLASTIC FLIP CAP F FF58 YELLOW**
815202006	PLASTIC FLIP CAP F FF58 BLUE**
815203006	PLASTIC FLIP CAP F FF58 BLACK**
815204006	PLASTIC FLIP CAP F FF58 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service