F IRBO14E NPT*

Codice articolo: **804501202** / **Female** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style Poppet	**Body size** 1/4"
Sealing EPDM	**Interchange** ISO 7241 B
Connection system Pull back the sleeve and push	**Disconnection system** Pull back the sleeve
Material Brass	**Locking mechanism** Locking ball
Disconnectable under pressure No	**Thread** FEMALE THREAD NPT (ANSI B.1.20.1)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F
Applications Drilling Rig, Coil Tubing Unit, Steel Mill, Test Bench, Chemical Pharma, Others, Die Casting, Injection Moulding, Electric Vehicles, Hydraulic Power Units, Food & Beverage, Semiconductors, Oil & Gas	

Performance	METRIC
ISO DN (mm)	6.3
Max. Flow suggested (l/min)	24
Max. Operating pressure - coupled (Mpa)	20
Operating pressure - uncoupled (MPa)	20
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	100
Connect force (N)	60
Disconnect force (N)	30
Spillage (ml)	0.33

Dimensions	METRIC
Port (A)	1/4"
Overall length M+F (mm)	70,7
Length (mm)	57
Max. diameter (mm)	27
Weight (kg)	0,13

Related products

Product code	Type	Product name
804501203	Maschio	M IRBO14E NPT

Spare kits

Product code	Product name
815700228	SPARE KIT OR EPDM+BK F ISOB 14 **

Caps

Product code	Product name
815000032	PLASTIC PLUG F ISO-B 14 RED
815003032	PLASTIC PLUG F ISO-B 14 BLACK **

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service