M IRBO14E NPT*

Codice articolo: **804501203** / **Male** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style Poppet	**Body size** 1/4"
Sealing EPDM	**Interchange** ISO 7241 B
Connection system Pull back the sleeve and push	**Disconnection system** Pull back the sleeve
Material Brass	**Locking mechanism** Locking ball
Disconnectable under pressure No	**Thread** FEMALE THREAD NPT (ANSI B.1.20.1)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F

Applications
Drilling Rig, Coil Tubing Unit, Steel Mill, Test Bench, Chemical Pharma, Others, Die Casting, Injection Moulding, Electric Vehicles, Hydraulic Power Units, Food & Beverage, Semiconductors, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	6.3
Max. Flow suggested (gpm)	6.36
Max. Operating pressure - coupled (psi)	2900
Operating pressure - uncoupled (psi)	2900
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	13.5
Disconnect force (lbf)	6.75
Spillage (ml)	0.33

Dimensions	IMPERIAL
Port (A)	1/4"
Overall length M+F (in)	2,78
Length (in)	1,38
Max. diameter (in)	0,56
Weight (lb)	0,09

Related products

Product code	Type	Product name
804501202	Femmina	F IRBO14E NPT

Caps

Product code	Product name
815000033	PLASTIC CAP M ISO-B 14 RED
815003033	PLASTIC CAP M ISO-B 14 BLACK **

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service