


# F IRBX34E BSP*

Codice articolo: **804600208** / **Female** / ***Prodotto disponibile su richiesta**






| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>3/4" |
| **Sealing**<br>EPDM | **Interchange**<br>ISO 7241 B |
| **Connection system**<br>Pull back the sleeve and push | **Disconnection system**<br>Pull back the sleeve |
| **Material**<br>Stainless steel (AISI 316L) + Retainer in Brass | **Locking mechanism**<br>Locking ball |
| **Disconnectable under pressure**<br>No | **Thread**<br>FEMALE THREAD BSPP (ISO 1179-1) |
| **Connectable under residual pressure**<br>No | **Temperature**<br>-40 / +150 °C; -40 / +302 °F |
| **Applications**<br>Drilling Rig, Coil Tubing Unit, Rail, Steel Mill, Test Bench, Chemical Pharma, Marine, Others, Die Casting, Injection Moulding, Electric Vehicles, Hydraulic Power Units, Defence, Food & Beverage, Semiconductors, Oil & Gas | |

| Performance | METRIC |
|---|---|
| ISO DN (mm) | 19 |
| Max. Flow suggested (l/min) | 148 |
| Max. Operating pressure - coupled (Mpa) | 16 |
| Operating pressure - uncoupled (MPa) | 16 |
| Burst pressure - coupled (MPa) | 80 |
| Burst pressure - uncoupled (MPa) | 80 |
| Connect force (N) | 135 |
| Disconnect force (N) | 55 |
| Spillage (ml) | 9.4 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 3/4" |
| Overall length M+F (mm) | 111,1 |
| Length (mm) | 90,1 |
| Max. diameter (mm) | 50 |
| Weight (kg) | 0,58 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 804600209 | Maschio | M IRBX34E BSP |

## Spare kits

| Product code | Product name |
|---|---|
| 815700234 | SPARE KIT OR EPDM+BK F ISOB 34 ** |

## Caps

| Product code | Product name |
|---|---|
| 815000038 | PLASTIC PLUG F ISO-B 34 RED |
| 815003038 | PLASTIC PLUG F ISO-B 34 BLACK ** |

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service