
# M APM15 BR6.5/57 3/4 BSP*

Codice articolo: **805100013** / **Male** / ***Prodotto disponibile su richiesta**




| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>5/8" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 |
| **Interchange**<br>ISO 16028 | **Connection system**<br>Push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD BSPP (ISO 1179-1) | **Connectable under residual pressure**<br>Pressure in male side only |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Earth Moving, Leather, Utensili idraulici, Hydraulic Power Units, Others, Test Bench, Rail, Road Construction, Material Handling, Foundation, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Agricultural Attachments, Agricultural Machinery, Earth moving, Agriculture, Vehicles, Oil & Gas |

| Performance | METRIC |
|---|---|
| ISO DN (mm) | 16 |
| Max. Flow suggested (l/min) | 148 |
| Max. Operating pressure - coupled (Mpa) | 33 |
| Operating pressure - uncoupled (MPa) | 33 |
| Burst pressure - coupled (MPa) | 100 |
| Burst pressure - uncoupled (MPa) | 120 |
| Connect force (N) | 160 |
| Disconnect force (N) | 50 |
| Spillage (ml) | 0.03 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 3/4" |
| Length (mm) | 95 |
| Max. diameter (mm) | 40 |
| Weight (kg) | 0,43 |

## Spare kits

| Product code | Product name |
|---|---|
| 815700341 | SPARE KIT OR NBR+BK M FF 58 |

## Caps

| Product code | Product name |
|---|---|
| 815100011 | PLASTIC CAP M FF58 RED |
| 816005009 | ALUMINUM CAP M FF58 NATURAL |
| 815101011 | PLASTIC CAP M FF58 YELLOW** |
| 815102011 | PLASTIC CAP M FF58 BLUE** |
| 815103011 | PLASTIC CAP M FF58 BLACK** |
| 815104011 | PLASTIC CAP M FF58 GREEN** |
| 815105011 | PLASTIC CAP M FF58 WHITE** |
| 815107011 | PLASTIC CAP M FF58 ORANGE** |
| 815110011 | PLASTIC CAP M FF58 MAGENTA** |

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service