
# F A13HDSS 3/4 BSP*

Codice articolo: **808300030** / **Female** / ***Prodotto disponibile su richiesta**







| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>1/2" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 |
| **Interchange**<br>ISO 16028 | **Connection system**<br>Push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball + Safety lock | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD BSPP (ISO 1179-1) | **Connectable under residual pressure**<br>Pressure in male side only |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Foundation, Paper, Packaging, Leather, Utensili idraulici, Hydraulic Power Units, Others, Road Construction, Material Handling, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Earth moving, Vehicles, Oil & Gas |

| Performance | IMPERIAL |
|---|---|
| ISO DN (mm) | 12.5 |
| Max. Flow suggested (gpm) | 23.85 |
| Max. Operating pressure - coupled (psi) | 4785 |
| Operating pressure - uncoupled (psi) | 4785 |
| Burst pressure - coupled (psi) | 14500 |
| Burst pressure - uncoupled (psi) | 14500 |
| Connect force (lbf) | 38.25 |
| Disconnect force (lbf) | 12.375 |
| Spillage (ml) | 0.02 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | 3/4" |
| Overall length M+F (in) | F+D-0,68 |
| Length (in) | 3,3 |
| Max. diameter (in) | 1,5 |
| Weight (lb) | 1,05 |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service