

M AX21E 1 BSP*

Codice articolo: **808500219** / **Male** / ***Prodotto disponibile su richiesta**





Valving style Flat face	**Body size** 1"
Sealing EPDM	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F
Applications Die Casting, Semiconductors, Leather, Food & Beverage, Defence, Laser, Electric Vehicles, Digital Transmitters, Injection Moulding, Data Center, Others, Medical Devices, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail	

Performance	IMPERIAL
ISO DN (mm)	31.5
Max. Flow suggested (gpm)	100.17
Max. Operating pressure - coupled (psi)	4350
Operating pressure - uncoupled (psi)	4350
Connect force (lbf)	64.125
Disconnect force (lbf)	24.75
Spillage (ml)	0.03

Dimensions	IMPERIAL
Port (A)	1"
Overall length M+F (in)	7,35
Length (in)	4,02
Max. diameter (in)	2,35
Weight (lb)	2,03

Related products

Product code	Type	Product name
808500220	Femmina	F AX21E 1 BSP

Spare kits

Product code	Product name
815700333	SPARE KIT OR EPDM+BK M FF 100

Caps

Product code	Product name
815100015	PLASTIC CAP M FF100 RED
816005013	ALUMINUM CAP M FF100 NATURAL
815101015	PLASTIC CAP M FF100 YELLOW**
815102015	PLASTIC CAP M FF100 BLUE**
815103015	PLASTIC CAP M FF100 BLACK**
815104015	PLASTIC CAP M FF100 GREEN**
815105015	PLASTIC CAP M FF100 WHITE**
815107013	PLASTIC CAP M FF100 ORANGE**
815110013	PLASTIC CAP M FF100 MAGENTA**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service