
F AX17 3/4 SAE

Codice articolo: **808504114** / **Female**



Valving style Flat face	**Body size** 3/4"
Sealing FKM (VITON)	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)
Connectable under residual pressure No	**Temperature** -15 / +180 °C; +5 / +356 °F
Applications Chemical Pharma, Marine, Medical Devices, Others, Defence, Food & Beverage, Leather, Semiconductors	

Performance	METRIC
ISO DN (mm)	19
Max. Flow suggested (l/min)	200
Max. Operating pressure - coupled (Mpa)	33
Operating pressure - uncoupled (MPa)	33
Connect force (N)	255
Disconnect force (N)	80
Spillage (ml)	0.03

Dimensions	METRIC
Port (A)	1-1/16-12UN
Overall length M+F (mm)	167,5
Length (mm)	103,8
Max. diameter (mm)	48
Weight (kg)	1,08

Related products

Product code	Type	Product name
808504115	Maschio	M AX17 3/4 SAE

Caps

Product code	Product name
815100010	PLASTIC CAP F FF34 RED
815200008	PLASTIC FLIP CAP F FF34 RED
816005010	ALUMINUM CAP F FF34 NATURAL
815101010	PLASTIC CAP F FF34 YELLOW*
815102010	PLASTIC CAP F FF34 BLUE*
815103010	PLASTIC CAP F FF34 BLACK*
815104010	PLASTIC CAP F FF34 GREEN*
815105010	PLASTIC CAP F FF34 WHITE*
815107006	PLASTIC CAP F FF34 ORANGE*
815110006	PLASTIC CAP F FF34 MAGENTA*
815201008	PLASTIC FLIP CAP F FF34 YELLOW*
815202008	PLASTIC FLIP CAP F FF34 BLUE*
815203008	PLASTIC FLIP CAP F FF34 BLACK*
815204008	PLASTIC FLIP CAP F FF34 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service