
F IP38 L10

Codice articolo: **809408014** / **Female**



Valving style Poppet	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Push
Disconnection system Pull	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread MALE THREAD METRIC L - 24° CONE (ISO 8434-1 & DIN 2353)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
ISO DN (mm)	10
Max. Flow suggested (l/min)	46
Max. Operating pressure - coupled (Mpa)	30
Operating pressure - uncoupled (MPa)	30
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	100
Connect force (N)	75
Disconnect force (N)	30
Spillage (ml)	1.2

Dimensions	METRIC
Port (A)	M16x1.5
Overall length M+F (mm)	95,2
Length (mm)	65,5
Max. diameter (mm)	32
Weight (kg)	0,2

Spare kits

Product code	Product name
815700926	SPARE KIT OR NBR+BK F IP38

Caps

Product code	Product name
815000014	PLASTIC PLUG F ISO-A 38 RED
815001014	PLASTIC PLUG F ISO-A 38 YELLOW*
815002014	PLASTIC PLUG F ISO-A 38 BLUE*
815003014	PLASTIC PLUG F ISO-A 38 BLACK*
815004014	PLASTIC PLUG F ISO-A 38 GREEN*
815005014	PLASTIC PLUG F ISO-A 38 WHITE*
815007014	PLASTIC PLUG F ISO-A 38 ORANGE*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service