M I14D L8 SCHOTT

Codice articolo: **809410011** / **Male**

Valving style Poppet	**Body size** 1/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Push
Disconnection system Pull	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread MALE THREAD METRIC L SCHOTT - 24° CONE BULKHEAD (ISO 8434-1 & DIN 2353)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
ISO DN (mm)	6.3
Max. Flow suggested (l/min)	24
Max. Operating pressure - coupled (Mpa)	35
Operating pressure - uncoupled (MPa)	35
Burst pressure - coupled (MPa)	110
Burst pressure - uncoupled (MPa)	126
Connect force (N)	27
Disconnect force (N)	17
Spillage (ml)	0.3

Dimensions	METRIC
Port (A)	M14x1.5
Overall length M+F (mm)	120,5
Length (mm)	60
Max. diameter (mm)	11,9
Weight (kg)	0,06

Caps

Product code	Product name
815000001	PLASTIC CAP M ISO-A/IR14 RED
815001001	PLASTIC CAP M IR14 YELLOW*
815002001	PLASTIC CAP M IR14 BLUE*
815003001	PLASTIC CAP M IR14 BLACK*
815004001	PLASTIC CAP M IR14 GREEN*
815005001	PLASTIC CAP M IR14 WHITE*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service