M I38 L8 SCHOTT

Codice articolo: **809410013** / **Male**

Valving style Poppet	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Push
Disconnection system Pull	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread MALE THREAD METRIC L SCHOTT - 24° CONE BULKHEAD (ISO 8434-1 & DIN 2353)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	IMPERIAL
ISO DN (mm)	10
Max. Flow suggested (gpm)	12.19
Max. Operating pressure - coupled (psi)	4350
Operating pressure - uncoupled (psi)	4350
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	16.875
Disconnect force (lbf)	6.75
Spillage (ml)	1.2

Dimensions	IMPERIAL
Port (A)	M14x1.5
Overall length M+F (in)	4,85
Length (in)	2,41
Max. diameter (in)	0,68
Weight (lb)	0,18

Caps

Product code	Product name
815000003	PLASTIC CAP M ISO-A/IR38 RED
815001015	PLASTIC CAP M ISO-A 38 YELLOW*
815002003	PLASTIC CAP M IR38 BLUE*
815003003	PLASTIC CAP M IR38 BLACK*
815004003	PLASTIC CAP M IR38 GREEN*
815005003	PLASTIC CAP M IR38 WHITE*
815007015	PLASTIC CAP M ISO-A 38 ORANGE*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service