
# M I38 L10 SCHOTT

Codice articolo: **809410015** / **Male**




| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>3/8" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 |
| **Interchange**<br>ISO 7241 A | **Connection system**<br>Push |
| **Disconnection system**<br>Pull | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball | **Disconnectable under pressure**<br>No |
| **Thread**<br>MALE THREAD METRIC L SCHOTT - 24° CONE BULKHEAD (ISO 8434-1 & DIN 2353) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Agricultural Machinery, Agricultural Attachments, Agriculture |

| Performance | IMPERIAL |
|---|---|
| ISO DN (mm) | 10 |
| Max. Flow suggested (gpm) | 12.19 |
| Max. Operating pressure - coupled (psi) | 4350 |
| Operating pressure - uncoupled (psi) | 4350 |
| Burst pressure - coupled (psi) | 14500 |
| Burst pressure - uncoupled (psi) | 14500 |
| Connect force (lbf) | 16.875 |
| Disconnect force (lbf) | 6.75 |
| Spillage (ml) | 1.2 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | M16x1.5 |
| Overall length M+F (in) | 4,93 |
| Length (in) | 2,45 |
| Max. diameter (in) | 0,68 |
| Weight (lb) | 0,19 |

## Caps

| Product code | Product name |
|---|---|
| 815000003 | PLASTIC CAP M ISO-A/IR38 RED |
| 815001015 | PLASTIC CAP M ISO-A 38 YELLOW* |
| 815002003 | PLASTIC CAP M IR38 BLUE* |
| 815003003 | PLASTIC CAP M IR38 BLACK* |
| 815004003 | PLASTIC CAP M IR38 GREEN* |
| 815005003 | PLASTIC CAP M IR38 WHITE* |
| 815007015 | PLASTIC CAP M ISO-A 38 ORANGE* |

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service