
# F VD34 L15

Codice articolo: **809508024** / **Female**




| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>3/4" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 |
| **Interchange**<br>ISO 14541 | **Connection system**<br>Screw |
| **Disconnection system**<br>Unscrew | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Screw to connect | **Disconnectable under pressure**<br>No |
| **Thread**<br>MALE THREAD METRIC L - 24° CONE (ISO 8434-1 & DIN 2353) | **Connectable under residual pressure**<br>Pressure in one side |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Construction Equipment Attachments, Demolition, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Earth moving, Vehicles |

| Performance | IMPERIAL |
|---|---|
| ISO DN (mm) | 20 |
| Max. Flow suggested (gpm) | 39.22 |
| Max. Operating pressure - coupled (psi) | 5800 |
| Operating pressure - uncoupled (psi) | 5800 |
| Burst pressure - coupled (psi) | 14500 |
| Burst pressure - uncoupled (psi) | 14500 |
| Spillage (ml) | 5 |
| Manual connect torque (lbf ft) | 1.8425 |
| Manual disconnect torque (lbf ft) | 1.6214 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | M22x1.5 |
| Overall length M+F (in) | 4,67 |
| Length (in) | 3,15 |
| Max. diameter (in) | 1,65 |
| Weight (lb) | 1,03 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 809508025 | Maschio | M VD34 L15 |

## Spare kits

| Product code | Product name |
|---|---|
| 815700906 | SPARE KIT OR NBR+BK+EXT F VD34 |

## Caps

| Product code | Product name |
|---|---|
| 814900006 | PLASTIC CAP F VD34 RED |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service