F VD100 S38 SCHOTT

Codice articolo: **809511024** / **Female**

Valving style Poppet	**Body size** 1"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 14541	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** No
Thread MALE THREAD METRIC S SCHOTT - 24° CONE BULKHEAD (ISO 8434-1 & DIN 8353)	**Connectable under residual pressure** Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Earth moving, Vehicles

Performance	METRIC
Max. Flow suggested (l/min)	200
Max. Operating pressure - coupled (Mpa)	30
Operating pressure - uncoupled (MPa)	30
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	100
Spillage (ml)	14
Manual connect torque (Nm)	2.7
Manual disconnect torque (Nm)	2.2

Dimensions	METRIC
Port (A)	M52X2
Overall length M+F (mm)	194,7
Length (mm)	123
Max. diameter (mm)	60
Weight (kg)	1,16

Related products

Product code	Type	Product name
809511025	Maschio	M VD100 S38 SCHOTT

Spare kits

Product code	Product name
815700908	SPARE KIT OR NBR+BK+EXT F VD100

Caps

Product code	Product name
814900016	PLASTIC CAP F VD100 RED

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service