M VR38 S12

Codice articolo: **809609005 / Male**

Valving style Flat face non spill	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings ("Rohrleitung")	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** No
Thread MALE THREAD METRIC S - 24° CONE (ISO 8434-1 & DIN 2353)	**Connectable under residual pressure** Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Earth moving, Vehicles

Performance	IMPERIAL
ISO DN (mm)	10
Max. Flow suggested (gpm)	12.19
Max. Operating pressure - coupled (psi)	5800
Operating pressure - uncoupled (psi)	2900
Burst pressure - coupled (psi)	23200
Burst pressure - uncoupled (psi)	10150
Spillage (ml)	0.01
Manual connect torque (lbf ft)	1.474
Manual disconnect torque (lbf ft)	1.3266

Dimensions	IMPERIAL
Port (A)	M20X1.5
Overall length M+F (in)	4,31
Length (in)	2,46
Max. diameter (in)	1,52
Weight (lb)	0,64

Related products

Product code	Type	Product name
809609004	Femmina	F VR38 S12

Caps

Product code	Product name
814900013	PLASTIC CAP M VR38 RED

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service