
M VR34 S16

Codice articolo: **809609021** / **Male**



Valving style Flat face non spill	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings ("Rohrleitung")	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** No
Thread MALE THREAD METRIC S - 24° CONE (ISO 8434-1 & DIN 2353)	**Connectable under residual pressure** Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Earth moving, Vehicles

Performance	IMPERIAL
ISO DN (mm)	20
Max. Flow suggested (gpm)	56.18
Max. Operating pressure - coupled (psi)	5075
Operating pressure - uncoupled (psi)	2900
Burst pressure - coupled (psi)	20300
Burst pressure - uncoupled (psi)	10150
Spillage (ml)	0.4
Manual connect torque (lbf ft)	1.6214
Manual disconnect torque (lbf ft)	1.2529

Dimensions	IMPERIAL
Port (A)	M24X1.5
Overall length M+F (in)	6,07
Length (in)	3,39
Max. diameter (in)	2,68
Weight (lb)	1,87

Related products

Product code	Type	Product name
809609020	Femmina	F VR34 S16

Caps

Product code	Product name
814906017	ALUMINUM CAP M VR34 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service