
# F/NIPPLE VOF114 BSP

Codice articolo: **811200004 / Nipple**




| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>1-1/4" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 |
| **Interchange**<br>Similar couplings (Oil&Gas) | **Connection system**<br>Screw |
| **Disconnection system**<br>Unscrew | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Screw to connect | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD BSPP (ISO 1179-1) | **Connectable under residual pressure**<br>Pressure in one side |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Earth moving, Oil & Gas |

| Performance | METRIC |
|---|---|
| ISO DN (mm) | 31.5 |
| Max. Flow suggested (l/min) | 576 |
| Max. Operating pressure - coupled (Mpa) | 34.5 |
| Operating pressure - uncoupled (MPa) | 34.5 |
| Burst pressure - coupled (MPa) | 137.9 |
| Burst pressure - uncoupled (MPa) | 100 |
| Spillage (ml) | 42.3 |
| Manual connect torque (Nm) | 2.8 |
| Manual disconnect torque (Nm) | 1.9 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 1-1/4" |
| Overall length M+F (mm) | 197,9 |
| Length (mm) | 136,7 |
| Weight (kg) | 1,84 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 811200004 | Nipple | F/NIPPLE VOF114 BSP |

## Spare kits

| Product code | Product name |
|---|---|
| 815700960 | SPARE KIT OR NBR+BK F VOF114 |
| 815700961 | SPARE KIT INTERNAL PARTS F-M VOF114 |

## Caps

| Product code | Product name |
|---|---|
| 815405014 | ALUMINUM CAP N VOF114 NATURAL |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service